




FICHA TÉCNICA

Platina de acero inoxidable

Carbone Stainless Steel

DESCRIPCIÓN

Platina de acero inoxidable ASTM A276 T-304 de acabado satinado de 6 m de largo de 10 mm de espesor.

CÓDIGO

PLATINA 50MM. X 10MM

Marca: Carbone Stainless Steel

Acabado: Satinado

Espesor: 10 mm - 3/8"

Norma de Fabricación: ASTM A276

Ancho: 50 mm - 2"

Procedencia: Importado

Material: Acero Inoxidable T-304

EMPRESAS CARBONE S.A.				Certificate No. 00520180000021407							
Product Stainless Steel Flat Bars											
Specification ASTM A276											
Standard AISI 304				Finish Satin finish		Protect	-----				

Item No.	Product Description			Chemical Composition(%)							Mechanical Test				
	Dimensions		Quantity Pcs	Weight kgs	C	Si	Mn	P	S	Ni	Cr	Yield Strength	Tensile Strength	Elongation	HV
					MPa									%	
Specification				Standard	≤0.08	≤1.00	≤2.00	≤0.035	≤0.030	8.00 - 10.00	17-19	≥205	≥520	≥35	≤200
1	20 mm x 3 mm x 6000 mm		300	--	0.0421	0.32	0.716	0.0213	0.01620	8.081	17.4500	365	640	48	150
2	20 mm x 4 mm x 6000 mm		300	--	0.0421	0.32	0.716	0.0213	0.01620	8.081	17.4500	350	630	48	155
3	20 mm x 6 mm x 6000 mm		80	--	0.0421	0.32	0.716	0.0213	0.01620	8.081	17.4500	360	650	46	153
4	25 mm x 3 mm x 6000 mm		150	--	0.0421	0.32	0.716	0.0213	0.01620	8.081	17.4500	350	630	47	156
5	25 mm x 4 mm x 6000 mm		200	--	0.0421	0.32	0.716	0.0213	0.01620	8.081	17.4500	370	640	46	155
6	25 mm x 6 mm x 6000 mm		30	--	0.0421	0.32	0.716	0.0213	0.01620	8.081	17.4500	360	640	48	152
7	30 mm x 3 mm x 6000 mm		100	--	0.0421	0.32	0.716	0.0213	0.01620	8.081	17.4500	365	630	47	154
8	60 mm x 4 mm x 6000 mm		60	--	0.0421	0.32	0.716	0.0213	0.01620	8.081	17.4500	370	650	48	155
9	50 mm x 4 mm x 6000 mm		80	--	0.0421	0.32	0.716	0.0213	0.01620	8.081	17.4500	350	640	46	154
10	50 mm x 10 mm x 6000 mm		80	--	0.0452	0.32	0.723	0.0243	0.01722	8.092	17.4650	365	640	48	150
11	60 mm x 6 mm x 6000 mm		50	--	0.0421	0.33	0.716	0.0213	0.01620	8.081	17.4500	360	650	47	155
12	80 mm x 6 mm x 6000 mm		70	--	0.0421	0.32	0.716	0.0213	0.01620	8.081	17.4500	350	640	48	155
13	80 mm x 10 mm x 6000 mm		50	--	0.0421	0.32	0.716	0.0213	0.01620	8.081	17.4500	365	650	46	154

Remark

Note

*01 = Hardness Test
*02= Heat Treatment
*Gauge Length: 50mm

1 MPa=1 N/mm²=10bar=145psi=
10.2kgf/cm²

Visual Inspection(Surface) and Dimension Check : OK

Surveyor By	We hereby certify that material described herein has been manufactured and tested with satisfactory results in accordance with the requirement of the above material specification. The material described above has been found free of radiation by raw material supplier.	1.ISO 9001:2015 (No.01100056299) 2.PED/AD2000 (No.01202TWN/Q-050105) 3.ISO 14001:2004 (No.01104822096385) 4.OHSAS 18001:2007 (No.01113822096385)	
N/A			