



FICHA TÉCNICA

Producto: Flanche o Brida (SORF) Slip On Face - 150 Lbs

DESCRIPCIÓN: Flanche o Brida (SORF) Slip On Face - 150 Lbs de 3" de diametro de Acero Inoxidable 304 para uso industrial.

CÓDIGO: **W-20050**

Marca: Carbone Stainless Steel

Material: Acero Inoxidable T-304

Diámetro: 3" - 76.2 mm

Procedencia: Importado

Norma de Fabricación: ASTM Standard

EMPRESAS CARBONE S.A.		Certificate No. EN10204.3.1			
Product	Stainless Steel Pipe				
Specification	ASTMA312				
Standard	304	Finish	Mill Finish	Protect	PVC

Item No.	Product Description		Chemical Composition(%)													Tensile Test			
	Dimensions	Quantity Pcs	C	Si	Mn	P	S	Cr	Ni	N	Mo	Cu	Ti	Fe	Tensile Strength	Yield Strength	Elongation	Hardness (HV10)	TEST
																σb(MPa)	%		
Specification																σb0.2			
1	Tuberia s/c Sch 10 nominal 1/2"	30	0.041	0.35	1.06	0.034	0.001	18.2	8.05	---	---	---	---	---	528	226	46	177	GOOD
2	Tuberia s/c Sch 10 nominal 3/4"	12	0.041	0.35	1.06	0.034	0.001	18.2	8.05	---	---	---	---	---	528	226	46	177	GOOD
3	Tuberia s/c Sch 10 nominal 1"	30	0.041	0.35	1.06	0.034	0.001	18.2	8.05	---	---	---	---	---	528	226	46	177	GOOD
4	Tuberia s/c Sch 10 nominal 1 1/2"	20	0.041	0.35	1.06	0.034	0.001	18.2	8.05	---	---	---	---	---	528	226	46	177	GOOD
5	Tuberia s/c Sch 10 nominal 6"	10	0.044	0.34	1.08	0.033	0.001	18.25	8.04	---	---	---	---	---	528	226	46	177	GOOD
6	Tuberia s/c Sch 40 nominal 1 1/2"	20	0.041	0.35	1.06	0.034	0.001	18.2	8.05	---	---	---	---	---	528	226	46	177	GOOD
7	Tuberia s/c Sch 40 nominal 6"	2	0.044	0.34	1.08	0.033	0.001	18.25	8.04	---	---	---	---	---	528	226	46	177	GOOD
8	Tuberia s/c Sch 40 nominal 3"	8	0.022	0.36	0.84	0.031	0.003	18.21	8.05	---	---	---	---	---	534	223	43	172	GOOD
9	Tuberia c/c Sch 40 nominal 3"	6	0.045	0.53	0.88	0.026	0.005	18.0	8.05	---	---	---	---	---	528	226	46	177	GOOD
10	Codo 90 grados Sch 40 1"(W-20002)	70	0.045	0.87	1.01	0.035	0.004	18.14	8.02	---	---	---	---	---	528	226	46	177	GOOD
11	Bushing hex NPT 1/4" x 3/8" (W-2008409)	100	0.066	0.484	0.829	0.036	0.005	18.19	8.078	---	0.087	0.087	0.003	72.13	528	226	46	177	GOOD
12	Niple NPT 1/4"200PCS(W-20104)	200	0.066	0.484	0.829	0.036	0.005	18.19	8.078	---	0.087	0.087	0.003	72.13	528	226	46	177	GOOD
13	Brida Slip on # 150 2"	20	0.45	0.38	1.14	0.037	0.001	18.33	8.3	---	---	---	---	---	528	226	46	177	GOOD
14	Brida Slip on # 150 3"	60	0.52	0.34	1.18	0.034	0.002	18.32	8.06	---	---	---	---	---	528	226	46	177	GOOD
15	Brida Slip on # 150 4"	60	0.045	0.38	1.14	0.037	0.001	18.33	8.03	---	---	---	---	---	528	226	46	177	GOOD
16	Valvula Mariposa 2"	60	0.053	0.37	1.13	0.031	0.001	18.21	8.05	0.049	---	---	---	---	528	226	46	177	GOOD
17																			
18																			
19																			
TOTAL:		708																	

Remark

Note

Visual Inspection(Surface) and Dimension Check : OK

Surveyor By	We hereby certify that material described herein has been manufactured and tested with satisfactory results in accordance with the requirement of the above material specification. The material described above has been found free of radiation by raw material supplier.	1.ISO 9001:2015 (No.01100056299) 2.PED/AD2000 (No.01202TWN/Q-050105) 3.ISO 14001:2004 (No.01104822096385) 4.OHSAS 18001:2007 (No.01113822096385)
N/A		