



FICHA TÉCNICA

Producto: **Válvula roscada de 3 pcs de acero inoxidable**

DESCRIPCIÓN: Válvula roscada de 3 pcs de acero inoxidable - ASTM Standart de medida 1 1/2" - 38 mm. Soporta una presión nominal de PN1.6, 2.5, 4.0, 6.4 MPa. Su fuerza de presión de prueba es de DT2.4, 3.8, 6.0, 9.6 MPa. Su fuerza de presión de sellado a baja presión es de 0.6 MPa. La temperatura de Trabajo es de -40° - 180° C. Su rosca es NPT y soporta una presión #150

CÓDIGO: W-20139

Marca: Carbone Stainless Steel

Medida: 1 1/2" - 38 mm

Presión Nominal: PN1.6, 2.5, 4.0, 6.4 MPa

Fuerza de presión de prueba: DT2.4, 3.8, 6.0, 9.6 MPa

Fuerza de presión de sellado (baja presión): 0.6 MPa

Temperatura de Trabajo: -40° - 180° C

Norma de Fabricación: ASTM Standart

Material: Acero Inoxidable T-304

Presión: #150

Rosca: NPT

Procedencia: Importado

EMPRESAS CARBONE S.A.		Certificate No. EN10204.3.1					
Product	Stainless Steel						
Specification	AISI304						
Standard	ASTM Standart	Finish	Mill Finish		Protect		

Item No.	Product Description		Chemical Composition(%)												Tensile Test				
	Dimensions	Quantity Pcs	C	Si	Mn	P	S	Cr	Ni	N	Mo	Cu	Ti	Fe	Tensile Strength	Yield Strength	Elongation	Hardness (HV10)	TEST
															σb(MPa)		%		
Specification																σb0.2			
1	Tuberia c/c Sch 40 nominal 2" Valvula 3 pcs NPT 1-1/2"	30	0.038	0.41	0.89	0.028	0.003	18.07	8.2	---	---	---	---	---	528	226	46	177	GOOD
2		10	0.05	1.00	1.1	0.025	0.01	18.1	8.1	---	---	---	---	---	528	226	46	177	GOOD
3																			
4																			
5																			
6																			
7																			
8																			
9																			
10																			
11																			
12																			
13																			
14																			
15																			
16																			
17																			
18																			
19																			
20																			

Remark

Note

Visual Inspection(Surface) and Dimension Check : OK

Surveyor By	We hereby certify that material described herein has been manufactured and tested with satisfactory results ip accordance with the requirement of the above material specification. The material described above has been found free of radiation by raw material supplier.	1.ISO 9001:2015 (No.01100056299) 2.PED/AD2000 (No.01202TWN/Q-050105) 3.ISO 14001:2004 (No.01104822096385) 4.OHSAS 18001:2007 (No.01113822096385)
N/A		